

# IM 2702SE

## MAIN SPECIFICATIONS

### GENERAL

Warm-up time	25 seconds
First copy speed: BW	6.5 seconds
Continuous output speed	27 ppm
Memory: standard	4 GB (2 GB mainframe + 2 GB Smart Operation Panel)
Memory: maximum	4 GB (2 GB mainframe + 2 GB Smart Operation Panel)
ARDF capacity	100 sheets
Weight	46.5 kg
Dimensions: W x D x H	587 x 581 x 677 mm
Power source	220 - 240 V, 50 - 60 Hz

### COPIER

Multiple copying	Up to 999 copies
Resolution	600 x 600 dpi
Zoom	From 25% to 400%

### PRINTER

Printer language	PCL5e PCL6 PostScript 3 (emulation)
Print resolution: maximum	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB2.0 Type B, USB Host 2.0
Mobile printing capability	Apple AirPrint Mopria®
Network protocol	TCP/IP
Windows® environments	Windows® 10/11, Windows® Server 2016/2019/2022/2025
Mac OS environments	Macintosh OS X v12 or later
SAP® environments	SAP® R/3® SAP® S/4®

### SCANNER

Scanning: B/W	50 ipm
Scanning: full colour	50 ipm
Resolution: maximum	1,200 dpi
Bundled drivers	Network TWAIN

### FAX

Compatibility	ITU-T (CCITT) G3
Transmission speed	3 seconds
Modem speed: maximum	33.6 Kbps

### PAPER HANDLING

Recommended paper size	Bypass tray: Custom Size paper: Width: 90 mm - 305 mm, Length: 148 mm - 600 mm
Paper input: standard	600 sheets
Paper input: maximum	1,600 sheets
Paper output: standard	250 sheets
Paper weight	Trays: 52 - 105 g/m <sup>2</sup> Bypass: 52 - 216 g/m <sup>2</sup>

### ECOLOGY

Power consumption: max.	< 1,550 W
Power consumption operation: B&W	500 W

### INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet paper tray  
2x 500-sheet paper tray  
One-bin tray

### OTHER OPTIONS

Fax unit  
Low cabinet  
ADF handle  
Bypass tray cover

# IM 2702SE

## MAIN SPECIFICATIONS

### CONSUMABLES

Toner (regular yield)	4,000 prints
Toner (high yield)	12,000 prints
Consumable yield based on 2p/j 6% coverage on A4	

For availability of models, options and software, please consult your local supplier.



### Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B  
1066 EP Amsterdam  
The Netherlands



+31 (0)20 5774111



[ricoh-europe.com](http://ricoh-europe.com)