




With a size boost and spec upgrade, the SickleFlow 200 ARGB is the newest option in our series. The reinforced frame structure and signature Air Balance fan blades reduces turbulence and noise while maintaining impressive air flow and pressure. The fan bearing is sealed to block out dust and prevent leakage, and enhancing lifespan and stability. The SickleFlow 200 ARGB has also implemented the new Addressable Gen 2 RGB support, giving you even more versatility with color customization, both through the Addressable Gen 2 RGB controller and Cooler Master's MasterPlus+ software.

# SICKLEFLOW 200 ARGB



### Fortified Structural Support

Sound absorbing materials offering peaceful cooling solution



### Two-Tier Sealing

Blocks out dust and prevents oil leakage for enhanced life span and performance



### Addressable Gen 2 RGB Lighting

Each individual LED can be customized in different color (Controller & Software needed)

**Air Balance Blades** – Signature fan blades with optimized curvature for improved air flow and air pressure.  
**Reinforced Frame** - Fortified square frame structure with added rib-support cuts turbulent flow and noise while increasing durability and efficiency.  
**Improved Bearing Sealant** – Two-tier sealing design blocks out dust and prevents oil leakage for enhanced life span and performance.  
**Vibrant Lighting** – Frosted fan blades enhance light dispersion for a stunning, colorful effect.  
**Addressable Gen 2 RGB** - Addressable Gen 2 RGB ready for vast range of versatile customization to your lighting.

## SPECIFICATIONS

Product Name	SickleFlow 200 ARGB	
Product Number	MFX-B3DN-08NP2-R1	
Exterior Color	Black	
Fan	Dimensions (L x W x H)	200 x 200 x 25 mm (7.9 x 7.9 x 1 inch)
	Profiles	Addressable Gen 2 RGB
	Speed (RPM)	0 ~ 800 RPM (PWM) ± 10%
	Airflow (CFM)	174.5m <sup>3</sup> /h (102.8 CFM )
	Noise Level (dBA)	15.7 dBA
	Bearing	Sleeve
	Pressure (mmH <sub>2</sub> O)	1.35 mmH <sub>2</sub> O
	MTTF	> 160,000 hours
	Power Connector	4-Pin (PWM)
	Rated Voltage (VDC)	12 VDC
	Rated Current (A)	0.2 A
	Safety Current	0.3 A
	Power Consumption	2.4 W
	RGB Connector	3-Pin ARGB
	RGB Rated Voltage	5 VDC
RGB Rated Current	0.4 A	
Weight	330 g (0.7lbs)	
Warranty	3 years	

## PACKING INFORMATION

EAN code	4719512124024
UPC code	884102096341
Net weight	0.36kg
Gross weight	0.52kg
Package dimension (L x W x H)	22.4 X 3.5 X 28 cm
Carton dimension (L x W x H)	57.5 x 38.5 x 25 cm
Units/CTN	20

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	6400	32	N/A
40'	12800	32	N/A
40 HQ	14400	36	N/A